



EPOXY GLUE EX-901

Description

COVERAGE:

Varies according to applications

DIRECTION OF MIXING :

Ensure that the surface is dry, clean and free of oil, grease and other contaminants. Mix the resin and hardener, in the ratio 1:0:8 by weight, on a dry and clean flat surface. Thoroughly mix the materials until a homogeneous paste with a uniform colour is achieved.

KEY BENEFITS

- Suitable for any materials
- Excellent strength, toughness and resistance
- Great resistance to chemical attack and moisture
- Excellent electrical insulation properties
- No volatiles on curing
- Minimal Shrinkage

INSTALLATION:

Ensure that the surface to be applied is dry, clean and free of oil, grease and other contaminants. Apply the mixed material using a spatula on the surface to be adhered. It should be used within its pot life period. Ensure even levelling while affixing both substrates. After applying the paste, ensure that the substrate is held in place with a suitable support for a minimum 8 to 9 hours. Now leave it for a minimum of 24 hours to achieve its maximum strength.

PRECAUTION:

- – Keep out of reach of children
- – Swallowing is not allowed
- – Seek doctors advice if in case of any accidents
- – Make sure to keep no contact with eyes and skin
- – Do not release into the environment
- – Wear protective clothes like gloves, eye and Face protection should be used during mixing and applying

APPLICATION AREAS:

UltraBONDEPOXY GLUE 901 Resin and Hardener both create a strong adhesion with similar and dissimilar substances such as glass, metal laminate, wood, textile and natural stone.

AVAILABLE PACK SIZES

EPOXY GLUE 901 Resin and Hardener is available in 100 ml x 40 Pcs/ Box

PRODUCT SPECIFICATIONS

Colour: White

Storage: Up to 12 months in manufacturers sealed containers stored in a cool dry place and away from high temperatures.

Shelf Life : 18 month from manufacturing date