



## ULTRABOND MASTIC EX-3003

### Description

## COVERAGE:

ULTRABOND MASTIC EX-3003s linear meter per kg of sealant

## DIRECTION OF MIXING:

The sealant can be applied using a spatula or trowel. As the product is solvent, it is recommended to mix the contents of the pail with a paddle mixer for a few minutes before the application to ensure a homogenous mix. The Sealant application should start from the bottom of the joint/groove and continue to the top. Immediately tool the joint with the spatula or putty knife to smoothen and compress the sealant to affect the total contact with joint surfaces. The putty knife shall be moistened with a cleaning solvent to prevent the sealant from adhering to the knife and ensuring a smooth and neat finish.

### KEY BENEFITS

- Easy to apply
- Flexible joint sealant
- Stability at high ambient Temperatures
- Excellent Adhesion
- Strong durable bond
- Single component

### INSTALLATION:

The surface must be free from all dirt, dust, and loose material. Any oil and grease contamination must be removed completely. The surface must be made dry before the application of the sealant. Masking before application of primer and sealant, apply masking tape to the adjacent sides of the joints for

getting a neat finish and to avoid the spilling over of the sealant on the edges. Priming under normal circumstances is not required. However, for very dry and porous surfaces, it is recommended to apply one coat of a solvent-based bitumen primer. Similarly, for joints subjected to continuous immersion, priming is recommended.

## **PRECAUTION:**

ULTRABOND MASTIC EX-3003 contains petroleum distillate that is flammable. So, keep away from fire, sparks, or other sources of ignition. Wear protective clothing, rubber gloves, masks, and safety goggles. Avoid repeated or prolonged contact. Remove all bitumen stains with a suitable cleaner that can remove oil or grease and then clean with soap and water. Avoid contact with eyes, it could cause irritations. If it affects the eye, flush with copious amounts of clean water. Inhalation of ULTRABOND MASTIC EX-3003 can cause dizziness, difficulty in breathing. Take safety measures.

## **APPLICATION AREAS :**

ULTRA BOND MASTIC EX-3003 is a single component solvent-based bitumen rubber mastic joint sealant. It is ideally suited for sealing and filling gaps and joints on roofs, pointing horizontal chases for waterproofing membranes and felts. ULTRA BOND MASTIC EX-3003 has excellent adhesion to concrete, brickwork, and most construction material substrates. The mastic sealant is modified with Non-Asbestos Fibre to make the sealant thixotropic and slump free when applied on vertical areas.

## **PRODUCT SPECIFICATIONS:**

- Color: Black
- Temperature : Up to 12 months in manufacturers sealed containers stored in a cool dry place and away from high temperatures.
- Shelf Life : 12 months from the date of original
- packing. Reseal the container after use and ensure product is stored as instructed on the label
- Pot-Life: Around 45 min
- Time for foot Traffic: 24hrs