



ULTRAPOXY EX 100

Description

DIRECTION OF MIXING :

Pour the contents of part A and Part B into a clean bucket. Mix Part A & Part B thoroughly for one minute with a trowel. Add atleast 3/4th of contents of part C Filler Powder and mix well. Add remaining powder slowly if required, to achieve required consistency.

INSTALLATION:

Before grouting, remove excess adhesive and debris from tile joints. Make sure to clean the tile surface with a damp sponge to remove dirt, dust, adhesive and stains. Fill the tile joint with the ULTRAPOXY EX 100 stain free grout with the putty blade. Holding the putty blade float perpendicular to the tiled surface, remove excess grout by drawing the putty blade across the surface at 45 degree to the grouted joints. Be sure to pack all joints full.

KEY BENEFITS:

- Very easy to apply
- Water-resistance
- Easy to compact and fill joints
- Strong and durable
- Uniform colour
- Non-toxic
- Antibacterial and anti-fungal

PRECAUTION:

Wear protective clothes such as gloves and goggles whilst handling the product. Wearing long sleeve

overall, safety shoes and face mask is recommended for maximum safety. Reseal all containers after use and ensure product is stored as instructed on the safety section of the labelling. Treat any splashes to the skin or eyes with fresh water immediately. Should any of the products are accidentally swallowed, do not induce vomiting, but call for medical assistance immediately.

APPLICATION AREAS :

ULTRAPOXY EX-100 is a three-compound stain free grout for floor and walls. It is a chemical-resistant grout for the complete finishing of your floors and wall joints. It provides strong adhesion to tiles and it is a strong water repellent. It is recommended to suit your concrete repair and joint filling needs. ULTRAPOXY EX-100 can be used for both internal and external purpose. It can be mainly used in kitchens bathrooms water bodies, operation theatre, sterilisation rooms etc.

AVAILABLE PACK SIZES:

ULTRAPOXY EX-100 is available in 1 kg and 5 kg containers.

PRODUCT SPECIFICATIONS

Colour: 20 Colours

Storage: Up to 12 months in manufacturers

sealed containers stored in a cool dry place

and away from high temperature.

Shelf Life :12 months from the date of original packing. Reseal the container after use and ensure product is stored as instructed on the label.

Pot-Life: Around 45min

Time for foot Traffic : 24 hrs

Ultra Bond