



## ULTRAPOXY EX-200

### Description

## QUANTITY & DIRECTION OF MIXING :

Pour the contents of part A and Part B into a clean bucket. Mix Part A & Part B thoroughly for one minute with a trowel.

## INSTALLATION:

Before grouting, remove excess adhesive and debris from tile joints. Make sure to clean the tile surface with a damp sponge to remove dirt, dust, adhesive and stains. Fill the tile joint with the ULTRAPOXY EX-200 stain free grout with the putty blade. Holding the putty blade float perpendicular to the tiled surface, remove excess grout by drawing the putty blade across the surface at 45 degree to the grouted joints. Be sure to pack all joints

### KEY BENEFITS:

- Very easy to apply
- Water-resistance
- Easy to compact and fill joints
- Strong and durable
- Uniform colour
- Non-toxic
- Antibacterial and anti-fungal

### PRECAUTION:

Wear protective clothes such as gloves and goggles whilst handling the product. Wearing long sleeve overall, safety shoes and face mask is recommended for maximum safety. Reseal all containers after use and ensure product is stored as instructed on the safety section of the labelling. Treat any

splashes to the skin or eyes with fresh water immediately. Should any of the products are accidentally swallowed, do not induce vomiting, but call for medical assistance immediately. [Read More](#)

## **APPLICATION AREAS:**

ULTRAPOXY EX-200 is a Two-compound stain free grout for floor and walls. It is a chemical-resistant grout for the complete finishing of your floors and wall joints. It provides strong adhesion to tiles and it is strong water repellent. It is recommended to suit your concrete repair and joint filling needs.

ULTRAPOXY EX-200 can be used for both internal and external purpose. It can be mainly used in kitchens bathrooms water bodies, operation theatre, sterilisation rooms etc.

## **AVAILABLE PACK SIZES**

ULTRAPOXY EX-200 is available in 1 kg and 5 kg containers.

## **PRODUCT SPECIFICATIONS**

- Color: 20 Colours
- Storage: Up to 12 months in manufacturers sealed containers stored in a cool dry place and away from high temperature.
- Shelf Life: 12 months from the date of original packing. Reseal the container after use and ensure product is stored as instructed on the label
- Pot-Life: Around 45min
- Time for foot Traffic : 24 hrs