



ULTRA BOND WALL PRIMER EX 3100
WALL PRIMER FOR INTERIOR & EXTERIOR



DESCRIPTION

EX 3100 Wall Primer is a water thinnable, superior grade water based wall primer which provides long lasting protection to masonry surface and enhances the aesthetic appearance of the top coat. It is an air drying primer for masonry wall and ceiling, providing a hard and tough film. EX 3100, 2 in 1 Wall Primer is suitable for interior and exterior use. It does not require curing and is a mandatory part of the painting system. It is manufactured with a special type of acrylic binder and micro fine pigments along with extenders and different types of additives.

USAGE AREAS

Designed for interior and exterior surfaces

- Wall and ceiling.
- On wall putty applied surfaces.
- Masonry surfaces.
- Concrete surfaces.

FEATURES & BENEFITS

- Excellent opacity and whiteness.
- Does not chalk and can be applied on adequately cured fresh plaster.
- Does not require curing with water.
- Provides excellent adhesion to top coat emulsions.
- Prevents peeling off of top coat emulsions.

TECHNICAL SPECIFICATION

Base	Acrylic Emulsion
Appearance	Liquid
Colour	White
Specific Gravity	1.38±.02
Solid	42-44 %
pH	8.0-9.0
Recommended dilution	Up to 75 %

Note: Test results are indicative as per test method specified in standard. Test result may vary as per substrate, site condition & testing machine etc. Actual field performance will depend on installation method and site condition.

SURFACE PREPARATION

NEW CONCRETE, MASONRY OR PLASTER :

New concrete, masonry or plaster surfaces must be allowed to cure completely. It is recommended to allow 28 days as the curing time for new masonry surfaces.

CLEANING

Ensure that the surface to be primed is free from any loose paint, dust or grease. Any previous growth of fungus, algae or moss needs to be removed thoroughly by vigorous wire brushing and cleaning with water. Always ensure the wall to be primed is dry and devoid of any loosely adhering cement.

FILLING

Surface imperfections such as holes, dents, fine cracks are to be filled with plaster or crack filler.

APPLICATION INSTRUCTIONS

Apply 1-2 coats by diluting EX 3100 primer up to 50 to 75 % with fresh water. A gap of 4 – 5 hours should be given between two coats.

PACKAGING

10 Litre, 20 Litre.

COVERAGE

Approximately 100-150 sft/liter on smooth masonry surface by Brushing.

* Coverage may vary depending upon the texture and porosity of the surface.

HEALTH & SAFETY

Avoid contact with eyes or prolonged contact with skin. It is recommended to use rubber hand gloves & safety goggles. In case of contact with eyes or skin, rinse immediately with plenty of clean water and seek medical advice. Keep out of reach of children.

SHELF LIFE & STORAGE

Shelf life is 12 months from the date of manufacturing in unopened conditions. To be stored in original and unopened packaging in a cool and dry place away from direct sunlight.

PRECAUTIONS & LIMITATIONS

- Stir well before application.
- Do not apply when the surface temperature is below 10° C.
- Do not apply on damp surface.
- Do not overthin or overextend the brush.

For detailed material safety data sheet please contact the manufacturer

CUSTOMER CARE 1800 425 33 50

PEGADO FIXING SOLUTIONS PVT LTD

34/3, INDUSTRIAL DEVELOPMENT PLOT, DP, KAPPUR, PARAKKULAM, ANAKKARA P.O
PALAKKAD DIST, KERALA, PIN-679551

 info@myultrabond.com

 www.myultrabond.com