



HYDROLOCK BASE COAT EX 4200 **ACRYLIC EMULSON BASED LIQUID MEMBRANE**



DESCRIPTION

HYDROLOCK BASE COAT EX 4200 is used as a liquid applied damp proofing membrane in Sandwich construction in which latex film is protected during its intended lifetime. HYDROLOCK BASE COAT EX 4200 is a black pigmented compound, designed for use as a liquid applied membrane. The product has a bluish black colour but will turn into a black membrane when drying.

USAGE AREAS

Damp proofing of most porous substrate. Protection of foundation, basement, kitchen, bathrooms. Used as a Moisture barrier and damp proof membrane in sandwich construction application.

FEATURES & BENEFITS

- Single component, ready-to-use, brushable product.
- Provide good damp-proof membrane in sandwich construction.
- Water based non-toxic
- Non-flammable
- Resists attacks by Chloride and Sulphates.

TECHNICAL SPECIFICATION

Base	Acrylic Emulsion
Appearance	Liquid
Colour	Bluish Black
Specific Gravity	1.10±.01
Solid	42-44 %
pH	8.0

Note: Test results are indicative as per test method specified in standard. Test result may vary as per substrate, site condition & testing machine etc. Actual field performance will depend on installation method and site condition.

SURFACE PREPARATION

The substrate should be clean, free from powders or dust, grease , oils etc. Water jet cleaning is advisable if required. Do not apply on completed wet or water-soaked concrete or plaster surface. Do not apply on highly wet surface immediately after plastering or concreting. If it is completely dried, some wetting or semi saturation with water spray will help for good bonding.

APPLICATION INSTRUCTIONS

Hydrolock base coat EX 4200 can be applied by brush or roller on surfaces directly without any dilution. It is advised to apply minimum two coats. The second coat is applied only when the first coat is touch dry, this is usually possible in 1 hour after applying the first coat.

PACKAGING

20 Litre.

COVERAGE

Coverage depends upon the nature of the surface to be applied. But on average, smooth surface will give approx. 300-400 Sq.feet/20 Ltr in two coats.

* Coverage may vary depending upon the texture and porosity of the surface.

HEALTH & SAFETY

Avoid contact with eyes or prolonged contact with skin. It is recommended to use rubber hand gloves & safety goggles. In case of contact with eyes or skin, rinse immediately with plenty of clean water and seek medical advice.Keep out of reach of children.

SHELF LIFE & STORAGE

Shelf life is 12 months from the date of manufacturing in unopened conditions. To be stored in original and unopened packaging in a cool and dry place away from direct sunlight.

PRECAUTIONS & LIMITATIONS

- Not suitable for exposed area application.
- Do not dilute with water.
- EX 4200 is not designed for application over live leakage scenarios.

For detailed material safety data sheet please contact the manufacturer

CUSTOMER CARE 1800 425 33 50

PEGADO FIXING SOLUTIONS PVT LTD

34/3,INDUSTRIAL DEVELOPMENT PLOT,DP,KAPPUR,PARAKKULAM,ANAKKARA P.O
PALAKKAD DIST, KERALA,PIN-679551

 info@myultrabond.com

 www.myultrabond.com